

WHAT IS CLAIMED IS:

Sub #1
D1
5 1. A method for modeling the behavior of elements in a telecommunications network, comprising:

providing a node representing a network element;

storing in the node a service state for the node;

storing in the node a service state for a first parent node upon which the node is operationally dependent;

in response to a triggering occurrence, dynamically associating a second parent node with the node;

10 storing in the node a service state for the second parent node; and

in response to receiving a new service state for one of the parent nodes, redetermining the service state for the node based on the service states for the parent nodes.

15 2. The method of Claim 1, further comprising generating the second parent node in response to a triggering occurrence.

Sub #2
20 3. The method of Claim 1, wherein the network element is a physical element in the network and the parent nodes represent physical elements in the network.

25 4. The method of Claim 1, wherein the network element is a first physical element in the network, the first parent node represents a second physical element in the network upon which the first physical element is physically dependent, and the second parent node represents a logical element in the network upon which the first
30 physical element is logically dependent.

5. The method of Claim 1, further comprising, in response to the redetermined service state for the node being a new service state for the node:

5 determining any child nodes for the node, the child nodes operationally dependent upon the node; and
inserting the new service state for the node in each child node.

10 6. The method of Claim 5, further comprising redetermining a service state for each child node in response to the new service state for the node being inserted in the child node.

15 7. The method of Claim 1, further comprising:
storing in the node an operation state for the node;
and

in response to receiving a new operation state, redetermining the service state for the node based on the operation state and the parent service states.

20 8. The method of Claim 7, wherein the operation state is a composite state including at least one of a broken state, an in-service state, and a maintenance state for the node.

25

Sub
A3
C2

9. A method for modeling the behavior of elements in a telecommunications network, comprising:

providing a node representing a network element;
storing in the node a service state for the node;

5 storing in the node a service state for each of a plurality of parent nodes upon which the node is operationally dependent; and

10 in response to receiving a new service state for any of the parent nodes, redetermining the service state for the node based on the service states for each of the parent nodes.

15 10. The method of Claim 9, wherein the network element is a physical element in the network and the parent nodes represent physical elements in the network.

20 11. The method of Claim 9, wherein the network element is a first physical element in the network, one of the parent nodes represents a second physical element in the network upon which the first physical element is physically dependent, and one of the parent nodes represents a logical element in the network upon which the first physical element is logically dependent.

25 12. The method of Claim 9, further comprising, in response to the redetermined service state for the node being a new service state for the node:

determining any child nodes for the node, the child nodes operationally dependent upon the node; and

30 inserting the new service state for the node in each child node.

20

13. The method of Claim 12, further comprising redetermining a service state for each child node in response to the new service state for the node being inserted in each child node.

5

14. The method of Claim 9, further comprising:
storing in the node an operation state for the node;
and

10

in response to receiving a new operation state, redetermining the service state for the node based on the operation state and the parent service states.

15

15. The method of Claim 14, wherein the operation state is a composite state including at least one of a broken state, an in-service state, and a maintenance state for the node.

Sub
C3 AH
16. A network control system for modeling the behavior of elements in the network, comprising:

a node representing a network element;

5 a state store in the node for storing a service state for the node;

a parent state store in the node for storing a service state for each of a plurality of parent nodes upon which the node is operationally dependent; and

10 wherein the service state for the node is dependent upon the service states of the parent nodes.

17. The system of Claim 16, wherein the network element is a physical element in the network and the parent nodes represent physical elements in the network.

15 18. The system of Claim 16, wherein the network element is a first physical element in the network, one of the parent nodes represents a second physical element in the network upon which the first physical element is physically dependent, and one of the parent nodes represents a logical element in the network upon which the first physical element is logically dependent.

25 19. The system of Claim 16, the node further comprising:

a child list including a list of child nodes operationally dependent upon the node; and

30 wherein the node is operable to insert the service state for the node into each of the child nodes in the child list upon a change in the service state for the node.

22

20. The system of Claim 16, further comprising a state determiner operable to redetermine the service state for the node based on the service states for the parent nodes.

5

21. The system of Claim 16, the node further comprising:

an event list including a list of specified events;
and

10

an action list including an action to take in response to each event in the event list.

22. The system of Claim 21, further comprising:

15

the event list including a parent state event for a change in the service state for each of the parent nodes;

the action list including a corresponding action of calling a state determiner in response to each parent state event; and

20

the state determiner operable to redetermine the service state for the node based on the service states for the parent nodes.

Add C4